



Roll Cover

COMPANY WITH
ENVIRONMENTAL SYSTEM
CERTIFIED BY DNV GL
= ISO 14001 =

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =

Technical data sheet

PP CHIUSURA TRS. 90/RS3 PP CLEAR RECLOSABLE 90/RS3

Code: 131033

APPLICATION

This product can be used in the hygiene industry as closure of the packages of wet wipes. Specially designed to withstand repeated openings and closings and avoid the deterioration of the content.
The adhesive is resistant to the various liquid components contained in the package. Specific for PET packaging.
A careful evaluation of the functionality is necessary in own particular purpose.

FACE MATERIAL

Clear, glossy polypropylene film, with Top Coating for printing.

Technical characteristics

Thickness	92 µm
Weight	83 gr/sqm

ADHESIVE

RS3: Acrylic, removable adhesive, solvent based with average initial tack and final adhesion. High resistance to sunlight and high cohesion. High resistance to moisture.

Minimum application temperature: +10°C
Working temperature: -25°C +80°C
Food contact: not suitable

Properties

Coat weight	22 +/- 3 gr/sqm	FTM 12
Peel adhesion (180°) 20 min	4 - 7 N/inch	FTM 1 - St. STEEL
Peel adhesion (180°) 24 h.	5 - 8 N/inch	FTM 1 - St. STEEL
Quick stick	8 - 12 N/inch	FTM 9 - St. STEEL
Shear	> 60 hours	FTM 8 - St. STEEL

LINER

Super calendared, high density backing paper 73 gr/sqm. Constant thickness, good mechanical properties, suitable for automatic labelling. Good quality for optical scanning.

Technical characteristics

Thickness	63 µm	ISO 534
Weight	73 gr/sqm	ISO 536
Tensile strength M.D.	63 N/cm	ISO 1924
Transparency	42 %	DIN 53147
Release	6 +/- 3 gr/inch	FTM 3

Shelf life: 2 years when stored at 20-25°C, 40-50% relative humidity, in the original packaging. Don't expose the material at the direct sun light and to the heat sources.

This specification does not absolve users from performing its tests. The values indicated are the results of laboratory tests and under no circumstances must be taken to an absolute reference. It must therefore be deemed warranty or commitment. The user is solely responsible for all decisions about the use of the material. Roll Cover shall not be liable for any direct or indirect damages resulting from inappropriate use of the information contained in datasheets

Rev. May 2019