



PP NERO SOFT TOUCH 23/60 TCX
PP BLACK SOFT TOUCH 23/60 TCX

Code: 160036

APPLICATION

Film for lamination. Black, matt with "Soft Touch" effect.

FACE MATERIAL

Black, matt Polypropylene film, with Top Coating for printing.

Technical characteristics

Thickness	23 µm
Weight	20 gr/sqm

ADHESIVE

A2: Permanent acrylic adhesive, water based with low initial tack and low final adhesion. High resistance to sunlight and high cohesion.

Minimum application temperature: + 10°C
Working temperature: -40°C +150°C,
Food contact: suitable for direct food contact, approved by ISEGA.

Properties

Coat weight	17 +/- 2 gr/sqm	FTM 12
Peel adhesion (180°) 20 min	> 5 N/inch	FTM 1 – St. STEEL
Peel adhesion (180°) 24 h.	> 7 N/inch	FTM 1 – St. STEEL
Quick stick	> 5 N/inch	FTM 9 – St. STEEL
Shear	> 80 hours	FTM 8 – St. STEEL

LINER

Super calendared, high density backing paper 60 gr/sqm. Constant thickness, good mechanical properties, suitable for automatic labelling. Good quality for optical scanning.

Technical characteristics

Thickness	53 µm	ISO 534
Weight	61 gr/sqm	ISO 536
Tensile strength M.D.	50 N/cm	ISO 1924
Transparency	47 %	DIN 53147
Release	6 +/- 3 gr/inch	FTM 3

Shelf life: 2 years when stored at 20-25°C, 40-50% relative humidity, in the original packaging. Don't expose the material at the direct sun light and to the heat sources.

This specification does not absolve users from performing its tests. The values indicated are the results of laboratory tests and under no circumstances must be taken to an absolute reference. It must therefore be deemed warranty or commitment. The user is solely responsible for all decisions about the use of the material. Roll Cover shall not be liable for any direct or indirect damages resulting from inappropriate use of the information contained in datasheets.